

FOX FIRE

CLEANERS + SEALERS + CORROSION CONTROL

STAIN REPELLENT

MOISTURE, FOOD, OIL, GREASE AND GRAFFITI-RESISTANT REPELLENT

- Repels food stains, oil, grease and graffiti. Surface will continue to breathe. No change in surface appearance.
 - Deep penetration into the substrate. Excellent resistance to water intrusion.
 - Provides high resistance to alkali attack and to wind-driven rain.
-

DESCRIPTION: Foxfire Stain Repellent is clear, penetrating, breathable, VOC compliant, water, oil and graffiti resistant treatment for concrete, porous tile, paving, grout, some natural stone and other building materials. Foxfire Stain Repellent penetrates the surface and bonds chemically into the substrate, resulting in long term protection by reducing the ingress of water-borne and oil-based contaminants into the surface. Foxfire Stain Repellent is an excellent treatment around areas where food products such as mustard, ketchup, grease, milk, wine, beer and soft drinks are present. It is also suitable for use as an anti-graffiti treatment. Foxfire Stain Repellent keeps treated indoor and outdoor surfaces clean and easier to maintain.

APPLICATIONS: Foxfire Stain Repellent is suitable for a wide variety of applications, including building facades, floors, walls, swimming pool surrounds, patios, garages, kitchens and entertaining areas.

Foxfire Stain Repellent is designed to work without changing the natural appearance of the surface in order to repel and make a variety of stains easier to remove. It is suitable for indoor and outdoor use and does not flake or peel. It also will seal very small hairline cracks and provides protection from alkali attack, wind-driven rain and resistance to moisture.

LIMITATIONS: Foxfire Stain Repellent is not intended for below-grade waterproofing. It should not be applied if the surface temperature is below 40° F or above 100° F, if rain is expected within six hours following application, or if high winds or other conditions prevent proper application. If rain has preceded the application, the surface should be allowed to dry at least 24 hours. Caution should be taken to avoid contact with windows, motor vehicles, vegetation and adjacent surfaces. Test patterns should be performed before application to insure compatibility.

PRECAUTIONS: Stain Repellent should be kept closed when not in use and should be stored at temperatures between 35° F and 120° F. Mix well upon opening and prevent moisture

condensation from entering the container. Please refer to the Safety Data Sheet for more detailed information.

During application, precautions should be taken to protect the surrounding area from overspray and run off. Product will not etch glass but will leave a residue on non-porous surfaces.

TECHNICAL DATA: VOC: <50 g/l

APPLICATION METHOD: Before applying, it is recommended that tests be carried out on cleaned areas to determine usage and to test the effectiveness of the treatment. Depending on the porosity of each designated surface, coverage rates can vary. Typical coverage is approximately 80-300 square feet per gallon.

Before application, surfaces must be cleaned to remove all traces of dirt, dust, efflorescence, mold, salt, grease, oil, asphalt, laitance, curing compounds, paint, coatings and other contaminants. Depending upon the surface contamination, cleaning methods include shot-blasting, sandblasting, water-blasting and/or using chemical cleaners. The surface should be allowed to dry at least 24 hours after water-blasting.

Foxfire Stain Repellent should be applied by low-pressure (15 to 25 psi) pump equipment with a wet fan tip spray nozzle. Application can also be done using a nap roller (1") or a brush.

Horizontal Surfaces: Stain Repellent should be applied to refusal or until the material puddles or stands on the surface. After ten minutes sweep, squeegee, or mop any remaining material to dry areas.

Vertical Surfaces: Spray apply from top down using a low-pressure sprayer with a fan tip nozzle or with a roller with a minimum 1/2" nap. Flood surface until excess product runs down 6-8 inches below spray or roller pattern. A wet-on-wet re-application within 2-3 minutes is recommended for maximum coverage.

Disclaimer/Warranties: Neither manufacturer nor seller have any knowledge or control concerning the purchaser's use of the product. No expressed warranty is made by manufacturer or seller

with respect to the results of any use of the product or container that the product comes in. No implied warranties including, but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose are made with respect to the product. User shall rely on his or her own information and tests to be determine suitability of the product for the intended use and user assumes all risk and liability resulting from use of the product. Neither manufacturer nor seller assume any liability for personal injury, loss or damage resulting from the use of the

product. We do not suggest or guarantee that any hazards listed herein are the only ones which may exist. In event that the product shall prove defective, buyer's exclusive remedy shall be that the seller or manufacturer shall, upon written request of buyer, replace any quantity of the product which is proven to be defective or shall, at its option, refund the purchase price of the product upon return of the product. Manufacturer shall not be responsible for use of this product in a manner to infringe on any patent held by others.